7032T

1- sliding door underbench safety cabinet Type 30

COMPLIANCE

EN 14470-1

ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Tested and approved according to FM 6050



TECHNICAL FEATURES

Model	**7032T**	Shipping dimensions HxWxD (mm)	**835 x 1200 x 800**
Compliance	**EN 14470-1**	Ventilation	**Both inlet and outlet on the back wall of the cabinet**
Cabinet materials	**Melamine wood structure**	Openings diameter (mm)	**100**
Doors color	**light grey RAL 7035**	Number of compartments	**1**
Number of doors	**1**		**108.00**
Doors type	**sliding doors**	HS Code	**94036000**
Door closure	**manual closing**		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

- Perforated cover plate for cabinets 762T - 792T (Réf : C2T)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
7032T	635 x 1115 x 630	310 x 1000 x 475	60		0	50	108.00

Ecosafe
www.ecosafesa.com

Chemin des Champs Courbes 15
Zone industrielle de Vallaire Est
CH-1024 Ecublens (Switzerland)
www.ecosafesa.com - sales[at]ecosafesa.com