DLV53

Combination shower eyewasher for indoor use

COMPLIANCE

EN 15154-1, EN 15154-2, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

BUT ALSO...

- Compliant to the article R. 4224-14 of the Labour Code
- Delivered with the first-aid labelling
- EN 15154-1 and EN 15154-2 compliant
- Anti-dust caps for dusty environment
- Allows to rinse itself the body in case of chemical projection



TECHNICAL FEATURES

Model	**DLV53**	Shower head	**Green ABS RAL 6029**
Compliance	**EN 15154-1, EN 15154-2, NF X 15-221**		**19.00**
Shipping dimensions HxWxD (mm)	**350 x 250 x 860**	Pipe	**galvanised steel + green epoxy painted RAL 6029**
Use	**internal use**	Water inlet	**F1''**
	handle operating	Water outlet	**F1 1 / 4''**
Setting	**mounted on feet**	HS Code	**73242921**
Bowl	**Green ABS RAL 6029**		

OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DLV53	2115 x 850		11	75	19.00

Ecosafe
www.ecosafesa.com

Chemin des Champs Courbes 15
Zone industrielle de Vallaire Est
CH-1024 Ecublens (Switzerland)
www.ecosafesa.com - sales[at]ecosafesa.com